

O'RING RANGE



FEATURES

- LOW FRICTION CHAIN
- LONGWEARING O'RING DESIGN FOR INCREASED LIFE OF CHAIN
- HEAVY DUTY

NO HORSEPOWER LOSS WITH IRIS SPECIALLY DESIGNED O'RINGS

TYPE	LINK
428 OR	136
520 OR	120
525 OR	120
530 OR	120
630 OR	120

IRIS CHAIN APPLICATION GUIDE



REFERENCE	ROAD / TOURING								ROAD / RACE								MX					MX RACING					ENDURO					TRAIL		
	80	125	250	350	500	650	900		80	125	250	350	500	650	900		50	65	85	125	250	500	65	85	125	250	500	50	80	125	250	500	750	125
				450	600	750	1200					450	600	750	1200															650	900	250		
																																350		
415 GSX	✓															✓											✓	✓						
420 GSX	✓	✓															✓	✓									✓							
428 GSX	✓	✓																✓																
520 GSX		✓	✓	✓															✓	✓	✓											✓		
420 RXP	✓	✓						✓	✓								✓	✓					✓	✓			✓							
428 RXP	✓	✓						✓	✓									✓					✓				✓							
520 RXP		✓	✓	✓					✓	✓									✓	✓	✓				✓	✓	✓	✓	✓	✓	✓	✓		
428 HTP ORING	✓	✓						✓	✓																		✓							
520 HTP ORING		✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓						✓	✓				✓	✓	✓	✓	✓	✓	✓			
525 HTP ORING					✓	✓	✓				✓	✓	✓	✓															✓	✓				
530 HTP ORING					✓	✓	✓				✓	✓	✓	✓																✓				
630 HTP ORING					✓	✓	✓				✓	✓	✓	✓																				
520 XRING			✓	✓	✓	✓	✓				✓	✓	✓											✓	✓			✓	✓	✓				
525 XRING					✓	✓	✓				✓	✓	✓	✓														✓	✓					
530 XRING					✓	✓	✓				✓	✓	✓	✓															✓					
520 FB RING			✓	✓	✓	✓	✓				✓	✓	✓																	✓				
525 FB RING					✓	✓	✓				✓	✓	✓	✓																				
530 FB RING					✓	✓	✓				✓	✓	✓	✓																				

