

X'RING RANGE



FEATURES

- ▶ 1.5 TO 2 LONGER WEAR RESISTANCE TO NORMAL O'RING
- ▶ REDUCED FRICTION & INCREASED SEALING PERFORMANCE BY THE XRINGS 4 CONTACT POINTS

X RING HIGH PERFORMANCE & MAXIMUM LONG LIFE

TYPE	LINK
520 XR	120
525 XR	120
530 XR	120

IRIS CHAIN APPLICATION GUIDE



REFERENCE	ROAD / TOURING								ROAD / RACE								MX					MX RACING					ENDURO					TRAIL					
	80	125	250	350	500	650	900		80	125	250	350	500	650	900		50	65	85	125	250	500	65	85	125	250	500	50	80	125	250	500	750	125			
				450	600	750	1200					450	600	750	1200																650	900	250				
																																	350				
415 GSX	✓															✓												✓	✓								
420 GSX	✓	✓															✓	✓										✓									
428 GSX	✓	✓																✓																			
520 GSX		✓	✓	✓															✓	✓	✓																✓
420 RXP	✓	✓						✓	✓								✓	✓					✓	✓				✓									
428 RXP	✓	✓						✓	✓									✓						✓				✓									
520 RXP		✓	✓	✓					✓	✓									✓	✓	✓					✓	✓	✓		✓	✓	✓	✓	✓			✓
428 HTP ORING	✓	✓						✓	✓																			✓									
520 HTP ORING		✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓						✓	✓				✓	✓		✓	✓	✓	✓	✓	✓				
525 HTP ORING					✓	✓	✓					✓	✓	✓	✓																✓	✓	✓				
530 HTP ORING					✓	✓	✓					✓	✓	✓	✓																	✓	✓	✓			
630 HTP ORING					✓	✓	✓					✓	✓	✓	✓																						
520 XRING			✓	✓	✓	✓	✓					✓	✓	✓											✓	✓			✓	✓	✓	✓	✓				
525 XRING					✓	✓	✓					✓	✓	✓	✓																✓	✓	✓				
530 XRING					✓	✓	✓					✓	✓	✓	✓																	✓	✓	✓			
520 FB RING			✓	✓	✓	✓	✓					✓	✓	✓																		✓	✓	✓			
525 FB RING					✓	✓	✓					✓	✓	✓	✓																						
530 FB RING					✓	✓	✓					✓	✓	✓	✓																						

